

RPE-L480

聚乙烯樹脂

RECYCLED POLYETHYLENE RESINS



概述	Description
100%聚乙烯再生樹脂。	100% Recycled Polyethylene Resins.
特性	Characteristics
高流動性 卓越的光澤	High flowability Outstanding gloss
應用	Applications
1. 發泡 2. 射出 3. 改性	1. Foaming 2. Injection 3. Modified

物理性質 Physical Properties

項目 Properties	試驗方法 Test Method	數 值 Typical Value
熔融指數 Melt Index (g/10min) 2.16kg / 190°C	ASTM D1238	3-4
密度 Density (g/cm ³)	ASTM D792	0.92-0.935
斷裂點抗張強度 Tensile Strength (MPa)	ASTM D638	>13
斷裂點伸長率 Elongation at Break (%)	ASTM D638	>200

據本公司所知，上述資料應屬正確無誤，惟因使用時之情況非受本公司管制，所以本公司對上述所作之一切建議，恕不負保證之責，以上數據為平均值，謹提供作為參考。The information contained herein is, to our best knowledge, true and accurate. However, since conditions of use are beyond our control, all risks of such use are assumed by users. This data sheet provides average test values, which are only for referential use.

DATE : 2023.08.25

TYC ENVIRONMENTAL TECHNOLOGY CO., LTD. 域誠環保科技股份有限公司

Tel:886-2-28851353 Fax:886-2-28851320 Web:www.liankuaitaiwan.com E-mail:info@liankuai.com

Address: No. 200, Zhulu Rd., Zhutang Vil ., Zhutang Township, Changhua County 525, Taiwan (R.O.C.) 地址: 彰化縣竹塘鄉竹塘村竹鹿路200號

