



聚乙烯樹脂

RECYCLED POLYETHYLENE RESINS

概述	Description
聚乙烯再生樹脂 原材料再生比例 100%	Recycled Polyethylene Resins. Material from recycled sources 100%
特性	Characteristics
良好的加工性能	Good processability
應用	Applications
1. 吹膜 2. 改性	1. Blown film 2. Modified

物理性質 Physical Properties

項目 Properties	試驗方法 Test Method	數 值 Typical Value
熔融指數 Melt Index (g/10min) 2.16kg / 190°C	ASTM D1238	0.9-1.5
密度 Density (g/cm ³)	ASTM D792	0.91-0.925
斷裂點抗張強度 Tensile Strength (MPa)	ASTM D638	>20
斷裂點伸長率 Elongation at Break (%)	ASTM D638	>500
硬度 (蕭氏 D)Hardness (Shore D)	ASTM D2240	53D

據本公司所知，上述資料應屬正確無誤，惟因使用時之情況非受本公司管制，所以本公司對上述所作之一切建議，恕不負保證之責，以上數據為平均值，謹提供作為參考。The information contained herein is, to our best knowledge, true and accurate. However, since conditions of use are beyond our control, all risks of such use are assumed by users. This data sheet provides average test values, which are only for referential use.

Date: 2023.03.03